



Product Service


# CERTIFICATE

No. Z2 076729 0107 Rev. 07

**Holder of Certificate:** Seraphim Solar System Co.,Ltd.

No.1-2, Hengyao Rd, Henglin Zhen  
Wujin District  
213101 Changzhou  
PEOPLE'S REPUBLIC OF CHINA

**Certification Mark:**



**Product:**

**Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**  
**Mono-Crystalline Silicon Photovoltaic Module**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704061801217-07

**Valid until:** 2025-05-10

**Date,** 2020-08-06

( Zhulin Zhang )

# CERTIFICATE

No. Z2 076729 0107 Rev. 07

## Model(s):

1500 V DC Maximum System voltage,  
 Fire Safety Class C Modules:  
 SRP-xxx-6MA-HV (xxx=330-400, in step of 5);  
 SRP-xxx-6MB-HV (xxx=275-330, in step of 5);  
 SRP-xxx-E01A-HV (xxx=365-420, in step of 5);  
 SRP-xxx-E01B-HV (xxx=305-350, in step of 5);  
 SRP-xxx-BMA-HV (xxx=330-445, in step of 5);  
 SRP-xxx-BMB-HV (xxx=275-370, in step of 5);  
 SRP-xxx-BMC-HV (xxx=305-380, in step of 5);  
 SRP-xxx-E6A-HV (xxx=410-435, in step of 5);  
 SRP-xxx-E6B-HV (xxx=350-370, in step of 5);  
 SRP-xxx-BMZ-HV (xxx=425-450, in step of 5);

1000 V DC Maximum System voltage,  
 Fire Safety Class C Modules:  
 SRP-xxx-6MA (xxx=330-400, in step of 5);  
 SRP-xxx-6MB (xxx=275-330, in step of 5);  
 SRP-xxx-E01A (xxx=365-420, in step of 5);  
 SRP-xxx-E01B (xxx=305-350, in step of 5);  
 SRP-xxx-BMA (xxx=330-445, in step of 5);  
 SRP-xxx-BMB (xxx=275-370, in step of 5);  
 SRP-xxx-BMC (xxx=305-380, in step of 5);  
 SRP-xxx-E6A (xxx=410-435, in step of 5);  
 SRP-xxx-E6B (xxx=350-370, in step of 5);

1500 V DC Maximum System voltage,  
 Fire Safety Class A Modules:  
 SRP-xxx-6MA-BG (xxx=350-395, in step of 5);  
 SRP-xxx-6MB-BG (xxx=295-325, in step of 5);  
 SRP-xxx-BMA-BG (xxx=350-430, in step of 5);  
 SRP-xxx-BMB-BG (xxx=290-355, in step of 5);  
 SRP-xxx-BMC-BG (xxx=320-375, in step of 5);  
 SRP-xxx-BMA-DG (xxx=350-410, in step of 5);  
 SRP-xxx-BMB-DG (xxx=290-340, in step of 5);  
 SRP-xxx-BMC-DG (xxx=320-350, in step of 5);  
 SRP-xxx-BMZ-BG (xxx=425-450, in step of 5);  
 xxx stands for rated output power at STC.

## Parameters:

Safety Class:	Class II
Max. System Voltage:	1000V DC or 1500 V DC
Construction:	Framed or Frameless, with Junction box, cable and connector.
Fire Safety Class:	Class C or Class A according to UL790
PID Test Condition:	-1500V and -1000V, 288 h, 85% RH, 85°C according to IEC TS 62804-1:2015

## Tested according to:

IEC 61215-1(ed.1)  
 IEC 61215-1-1(ed.1)  
 IEC 61215-2(ed.1)  
 IEC 61730-1(ed.2)  
 IEC 61730-2(ed.2)  
 PPP 58042B:2015

## Production Facility(ies):

076729, 095290, 104590, 098633