



Product Service

CERTIFICATE

No. Z2 076729 0069 Rev. 01

Model(s):

SRP-xxx-6MA, xxx= 270 to 370 in step of 5
 SRP-xxx-6MB, xxx= 225 to 305 in step of 5
 SRP-xxx-6MC, xxx= 200 to 275 in step of 5
 SRP-xxx-6MD, xxx= 180 to 245 in step of 5
 SRP-xxx-6ME, xxx= 135 to 185 in step of 5
 SRP-xxx-5MA, xxx= 225 to 285 in step of 5
 SRP-xxx-5MB, xxx= 160 to 210 in step of 5
 SRP-xxx-5MC, xxx= 80 to 105 in step of 5
 SRP-xxx-BMA, xxx= 330 to 370 in step of 5
 SRP-xxx-BMB, xxx= 275 to 305 in step of 5
 SRP-xxx-BMC, xxx= 305 to 335 in step of 5
 SRP-xxx-BMD, xxx= 250 to 275 in step of 5
 SRP-xxx-BME, xxx= 220 to 245 in step of 5
 SRP-xxx-6PA, xxx= 245 to 335 in step of 5
 SRP-xxx-6PB, xxx= 205 to 275 in step of 5
 SRP-xxx-6PC, xxx= 185 to 250 in step of 5
 SRP-xxx-6PD, xxx= 125 to 165 in step of 5
 SRP-xxx-6PE, xxx= 165 to 220 in step of 5
 SRP-xxx-BPA, xxx= 310 to 355 in step of 5
 SRP-xxx-BPB, xxx= 255 to 295 in step of 5
 SRP-xxx-BPC, xxx= 280 to 325 in step of 5
 SRP-xxx-BPD, xxx= 225 to 265 in step of 5
 SRP-xxx-BPE, xxx= 195 to 235 in step of 5
 xxx is standing for rated output power at STC

Parameters:

Construction: Framed, with Junction box, Cable and Connectors.
 Application Class : Class A
 Maximum System Voltage: 1000 V DC
 Fire Safety Class: Class C

Tested according to:

IEC 61215(ed.2)
 IEC 61730-1(ed.1);am1;am2
 IEC 61730-2(ed.1);am1
 JIS Q 8901:2012

Production Facility(ies):

076729, 095290, 001283, 003273,
 090968, 096853, 098633, 004571

TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT